

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12

Version: 6.0

Page: 1/9

(30747420/SDS_GEN_CA/EN)

1. Identification

Product identifier used on the label

Slentex® 200/1

Recommended use of the chemical and restriction on use

Recommended use*: insulation

Unsuitable for use: None known

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Contact address:

BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1
CANADA
Telephone: +1 289 360-1300

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Chemical family: based on: glass fibres, amorphous silica, silicates

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12
Version: 6.0

Page: 2/9
(30747420/SDS_GEN_CA/EN)

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Glass, oxide, chemicals

CAS Number: 65997-17-3
Content (W/W): ≥ 35.0 - $< 45.0\%$
Synonym: No data available.

Silicon dioxide

CAS Number: 7631-86-9
Content (W/W): ≥ 30.0 - $< 40.0\%$
Synonym: Silicon dioxide

Wollastonite (Ca(SiO₃))

CAS Number: 13983-17-0
Content (W/W): ≥ 15.0 - $< 20.0\%$
Synonym: Wollastonite

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica

CAS Number: 68909-20-6
Content (W/W): ≥ 5.0 - $< 15.0\%$
Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

If inhaled:

After inhalation of decomposition products: Remove the affected individual into fresh air and keep the person calm. Seek medical attention.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Hold eyelids open to facilitate rinsing. If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., May cause slight skin irritation, especially with repeated or prolonged exposure.

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12

Version: 6.0

Page: 3/9

(30747420/SDS_GEN_CA/EN)

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
not applicable

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon monoxide, carbon dioxide, nitrogen oxides, carbon oxides, silicon oxides, metal oxides
Traces of the substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Rolls of material will retain heat within internal layers that may be a source of ignition after the fire is extinguished. To prevent re-ignition of interior, target center of fire with large amounts of water. In case of fire and/or explosion do not breathe fumes. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

No containment procedures are needed, as this product cannot spill or leak.

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Avoid dust formation. Goggles, dustmask, adequate ventilation.

Environmental precautions

No special precautions necessary.

Methods and material for containment and cleaning up

Sweep up or vacuum small pieces and dusts and place in appropriate container for disposal.

7. Handling and Storage

Precautions for safe handling

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12

Page: 4/9

Version: 6.0

(30747420/SDS_GEN_CA/EN)

Avoid the formation and deposition of dust. Ensure thorough ventilation of stores and work areas. Aerogel dust is hydrophobic, water is not an effective dust control agent. Trims and offcuts may be reused in secondary applications, otherwise scrap material should be packed for disposal. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid dust formation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Conditions for safe storage, including any incompatibilities

Segregate from acids. Segregate from bases. Segregate from oxidants. Segregate from reducing agents.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE)

Further information on storage conditions: Keep bags tightly sealed. Avoid deposition of dust.

Storage stability:

Protect from direct sunlight.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Silicon dioxide	OSHA PEL	TWA value 6 mg/m ³ ; TWA value 20 millions of particles per cubic foot of air ; TWA value 0.8 mg/m ³ ; The exposure limit is calculated from the equation, 80mg/m ³ /(%SiO ₂), using a value of 100% SiO ₂ . Lower percentages of SiO ₂ will yield higher exposure limits.
-----------------	----------	--

Glass, oxide, chemicals	ACGIH TLV	TWA value 5 mg/m ³ Inhalable fraction ; TWA value 0.2 fibers/cm ³ Fiber ;
-------------------------	-----------	---

crystalline silica	OSHA PEL	TWA value 0.05 mg/m ³ (Respirable dust); OSHA Action level 0.025 mg/m ³ (Respirable dust);
	ACGIH TLV	TWA value 0.025 mg/m ³ Respirable fraction ;

Advice on system design:

Avoid the formation and deposition of dust. Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Wear a NIOSH approved (or equivalent) particulate respirator if ventilation is inadequate to control dust.

Hand protection:

Wear impervious gloves.

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12

Version: 6.0

Page: 5/9

(30747420/SDS_GEN_CA/EN)

Eye protection:

Safety glasses with side-shields.

Body protection:

Standard work clothes and shoes.

General safety and hygiene measures:

Avoid inhalation of dusts. Handle in accordance with good industrial hygiene and safety practice.

Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	fabric, blanket
Odour:	slight odour, ammonia-like
Odour threshold:	0.6 - 53 ppm
Colour:	white
pH value:	No applicable information available.
Melting point:	not determined
Freezing point:	not determined
Boiling point:	No applicable information available.
Sublimation point:	No applicable information available.
Flash point:	No applicable information available.
Flammability:	not flammable
Lower explosion limit:	For solids not relevant for classification and labelling.
Upper explosion limit:	For solids not relevant for classification and labelling.
Autoignition:	No applicable information available.
Vapour pressure:	No applicable information available.
Density:	not applicable
Relative density:	1.12 - 1.20
Bulk density:	approx. 200 kg/m ³ (20 °C)
Vapour density:	not applicable
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Self-ignition temperature:	not self-igniting
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	not applicable
Viscosity, kinematic:	No applicable information available.
Solubility in water:	insoluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12

Version: 6.0

Page: 6/9

(30747420/SDS_GEN_CA/EN)

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is chemically stable.

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid dust formation. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

Thermal decomposition products: carbon oxides, nitrogen oxides, silicon oxides, metallic oxides

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Inhalation of particulates may cause respiratory tract irritation. Ingestion may cause gastrointestinal disturbances.

Oral

No applicable information available.

Inhalation

Inhalation of dust may cause irritation of the nose, throat and respiratory passages.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation / corrosion

Assessment of irritating effects: Contact with the eyes or skin may cause mechanical irritation.

Contact with powders or dusts may irritate the eyes, skin and respiratory tract.

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12
Version: 6.0

Page: 7/9
(30747420/SDS_GEN_CA/EN)

Sensitization

Assessment of sensitization: The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No known chronic effects. Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: The International Agency for Research on Cancer (IARC) has classified this substance as group 3, not classifiable as to its carcinogenicity to humans. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Glass, oxide, chemicals

Assessment of carcinogenicity: Based on available Data, the classification criteria are not met.

Information on: Silicon dioxide

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. IARC Group 3 (not classifiable as to human carcinogenicity).

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other Information

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Medical conditions aggravated by overexposure

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product.

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12
Version: 6.0

Page: 8/9
(30747420/SDS_GEN_CA/EN)

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Poorly biodegradable.

Elimination information

Poorly biodegradable.

Mobility in soil

Assessment transport between environmental compartments

Due to the product characteristics the test is impossible.

Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

13. Disposal considerations

Waste disposal of substance:

This product is not regulated by RCRA. Dispose of in accordance with national, state and local regulations.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Safety Data Sheet

Slentex® 200/1

Revision date : 2020/02/12
Version: 6.0

Page: 9/9
(30747420/SDS_GEN_CA/EN)

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released / exempt

Article

NFPA Hazard codes:

Health: 1 Fire: 0 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2020/02/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Slentex® 200/1 is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET